

Filter type:	NW650
Connection diameter:	2 ½"
Average flow rate (m³/h):	25 at ΔP 0,2 bar
Working pressure (bar):	10
Max. operating pressure (bar):	16
Max. operating temperature (°C):	50
Weight (kg):	7 / 8,6 (with packaging)
Packaging in mm (L x W x H):	760 x 315 x 227
Air drain screw:	Polyamide (PA) + polyester (2K)
Filter head:	Polypropylene (PP) + fiberglass
Bowl:	SAN
Wrench:	ABS
Collar:	PA
Flanges:	PP + 30% fiberglass
Seals:	O-ring butadiene-acrylonitrile (NBR)
Centrifugal vane + cap:	Polypropylene (PP) + 20% fiberglass + elastomer (2K)
Filtering support:	PP + 20% fiberglass
Valve adaptor:	PA
Filtering sleeve:	Polyester (non-washable) or nylon (washable)
Filtration surface (cm²):	1288
Original equipment:	Filtering sleeve 25 μm, wrench, drain-cock ¾" nickel-plated brass, 2 pressure gauges with glycerine 0-20 bar ¼" brass + 2 loose flanges 2 ½"
Option:	Stainless steel wall fixation 3mm
Filtering fineness available (μm):	Non-washable : 1 - 5 - 10 - 25 - 50 - 100
(packs of 5 sleeves)	Washable : 150 - 300

