

Filter type:	NW800
Connection diameter:	3"
Average flow rate (m ³ /h):	32 at ΔP 0,2 bar
Working pressure (bar):	10
Max. operating pressure (bar):	16
Max. operating temperature (°C):	50
Weight (kg):	7,4 / 9 (with packaging)
Packaging in mm:	760 x 315 x 227
Air drain screw:	Polyamide (PA) + polyester (2K)
Filter head:	Polypropylene (PP) + 20% fiberglass
Bowl:	SAN
Wrench:	ABS
Collar:	PA
Flanges:	PP + 30% fiberglass
Seals:	O-ring butadiene-acrylonitrile (NBR)
Centrifugal vane + cap:	Polypropylene (PP) + 20% fiberglass + elastomer (2K)
Filtering support:	PP + 20% fiberglass
Valve adaptor :	PA
Filtering sleeve:	Polyester (non-washable) or nylon (washable)
Filtration surface (cm ²):	1288
Original equipment:	Filtering sleeve 25 μm, wrench, drain-cock ¼ " nickel-plated brass, 2 pressure gauges with glycerine 0-20 bar ¼ " brass + 2 loose flanges 3"
Option:	Stainless steel wall fixation 3 mm
Filtering fineness available (μm):	Non-washable : 1 - 5 - 10 - 25 - 50 - 100
(packs of 5 sleeves)	Washable : 150 - 300

