

# TECHNICAL SHEET

FLECK  
INDUSTRIAL VALVE 2850



# TECHNICAL SHEET

OUR WEBSITE



## FLECK INDUSTRIAL VALVE 2850

### TECHNICAL CHARACTERISTICS

- Ideal for filter applications
- Power head: corrosion resistant and UV stable
- Valve body in brass
- Regeneration:
  - Manual
  - Timeclock: 7 or 12 days
  - Meter: delayed or immediate
  - Electronic timer



### VALVE SPECIFICATION

Material	Brass
Hydrostatic pressure	20 bar
Working pressure	1.8 - 8.5 bar
Working temperature	1 - 43 °C
Electrical rating	24 V - 50 Hz, other upon request
Protection index	IP 22

### FLOW RATE (3.5 BAR INLET - VALVE ALONE)

Continuous ( $\Delta p = 1$ bar)	11.6 m <sup>3</sup> /h
Peak ( $\Delta p = 1.8$ bar)	15 m <sup>3</sup> /h
CV*	13.2 gpm
MAXIMUM BACKWASH ( $\Delta P = 1.8$ BAR)	11.1 m <sup>3</sup> /h

\* Cv: Flow rate of valve alone in gpm at 0.07 bar pressure drop.

### DOWN FLOW REGENERATION

	Mechanical	Electronic
Cycles	Adjustable	Adjustable
Time available	164 min	99 min each cycle

## CONNECTIONS - DIMENSION

Inlet / outlet	1½" BSP
Distributor tube	50 mm (DN 40)
Riser tube cut: Target / Max / Min	0.25" below top of tank / Flush with top tank / 0.75" below
Drain line	1" NPT
Brine line (1650)	⅜"
Brine line (1710)	½"
Mounting base - Top	4" - 8 UN
Height (from the top of tank)	165 mm
<b>Tank size application (recommended)</b>	
Water softener	10 - 30" (250 - 760 mm)
Filters	10 - 24" (250 - 610 mm)

## METER

	Mechanical
Accuracy range (± 5%)	5 - 283 Lpm
Standard capacity range	2.5 - 40 m <sup>3</sup>
Extended capacity range	12 - 200 m <sup>3</sup>

## REGENERATION CYCLES

### Down flow

- 1) Backwash
- 2) Brine & slow rinse
- 3) Rapid rinse
- 4) Brine tank refill
- 5) Service

## OPTIONS

No water during regeneration	NBP
Regeneration	Manual
Mounting	Side Mount adapter
Electronic	
Filter	
Hot water	65°C meter / 82°C timeclock

[www.pentairaquaeurope.com](http://www.pentairaquaeurope.com)